

KM-2560

► print ► copy ► scan ► fax

MONOCHROME MULTIFUNCTIONAL FOR A3 FORMAT

COMFORTABLY HANDLES EVERYONE'S PROJECTS.

The KM-2560 multifunctional easily handles the various projects of a networked workgroup or tightly knit department by allowing simultaneous processing of multiple jobs. Universal design features give everyone in the workgroup equal access to productivity-enhancing technology, regardless of their strength or physical ability.

- Simultaneous multitasking and multi-sending
- 80 GB HDD
- 512 MB memory standard, upgradeable to 1 GB
- 25 pages per minute monochrome printing/copying
- Long-life components for outstanding reliability



Colour touch panel with intuitive menus and easy-to-view colour thumbnails.

Easy-to-open paper cassettes with ergonomically designed handles.



KM-2560

MONOCHROME MULTIFUNCTIONAL FOR A3 FORMAT

The KM-2560 incorporates extremely durable components that guarantee efficient and reliable operation to meet the demanding requirements of busy office environments. The KM-2560 provides effective productivity and maximises uptime whilst ensuring a minimum impact on the environment.

General

Technology: KYOCERA Laser, Mono component

Engine speed

Max. 25/12.5 pages per minute A4/A3

Resolution

600 x 600 dpi (copy), 1,800 dpi level x 600 dpi (copy, photo mode), 1,200 dpi quality (print)

Time to first copy: 4.7 seconds or less

Warm-up time: 29 seconds or less from power on

Power source: AC 220 ~ 240 V, 50/60 Hz

Power consumption

Printing: 560 W, Stand-by: 160 W, Power-Saving (ECOpower): 8.7 W

Noise (ISO 7779)

Printing/copying: 64.7 dB(A), Stand-by: 47 dB(A), Power-Saving (ECOpower): Immeasurably low

Dimensions (W x D x H)

Main unit: 570 x 620 x 767.2 mm

Weight: Main unit approx. 75 kg

Certifications

TÜV/GS, CE, ISO 15408

This product is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

Paper handling

All paper capacities quoted are based on a paper thickness of max. 0.11 mm. Please use paper recommended by KYOCERA under normal environmental conditions.

Input capacity

2 x 500-sheet universal paper feeder, 60–120 g/m², A3–A5R, folio, 200-sheet multi-purpose tray, 45–200 g/m², A3–A6R, folio, envelopes
Max. input capacity with options: 2,200 sheets

Duplex unit

Duplex as standard supports A3–A5, 60–80 g/m²

Output capacity: 250 sheets face-down

Copy functions

Max. original size: A3

Continuous copying: 1–999

Memory capacity

Standard 512 MB (max. 1 GB) + 80 GB HDD (system-shared)

Zoom range

25–400% in 1% steps (with DP-670: 25–200%)

Preset magnification ratios: 5R / 5E

Digital features

Interrupt output job, scan-once-print-many, electronic sort, rotate sort, rotate copy, N-up copy, split copy, cover mode, page numbering, box image overlay, margin shift, border erase

Exposure mode: Auto, manual: 7 or 13 steps

Image adjustments: Text + photo, text, photo

Your KYOCERA Business Partner:

Print functions (optional)

Processor: PowerPC 750Cxr / 400 MHz

Memory

Standard 512 MB (max. 1 GB) + 80 GB HDD (system-shared)

Emulations

PCL6 incl. P/L, KPDL 3 (PostScript 3 compatible)
Line Printer, IBM Proprinter X24E, Epson LQ-850, Diablo 630

Controller language: PRESCRIBE IIe

Fonts

80 outline fonts (PCL6), 136 PostScript KPDL 3 fonts, 1 bitmap font, 45 types of one-dimensional barcodes plus two-dimensional barcode (PDF-417)
Downloadable fonts: Kyocera, PCL + TrueType format, Type 1 + 3 format

Features

eMPS – for quick copy, proof and hold, private print, job storage and job management functionality

Interfaces

Standard interface: USB 2.0 (Hi-Speed), USB Host Interface dedicated for USB Flash Memory device, Fast Ethernet 10-Base-T/100Base-TX, CF slot

Multiple interface connection (MIC)

Allows simultaneous data transfer via up to four interfaces, with each interface having its own virtual printer.

Scan functions (optional)

Functionality

Scan-to-SMB/FTP, scan-to-email, scan-to-BOX, network TWAIN, BOX TWAIN

Scan speed

50 originals per minute in b/w (300 dpi/A4), 15 originals per minute in colour (300 dpi/A4)
30 originals per minute in b/w (600 dpi/A4), 15 originals per minute in colour (600 dpi/A4)

Scan resolution

600, 400, 300, 200, 200 x 400, 200 x 100 dpi (256 greyscales, 256 colour)*

Max. scan size: A3

Original recognition: Text, photo, text + photo, OCR

Interface: 10Base-T/100Base-TX

Network protocol: TCP/IP

File types: Mono: TIFF, PDF

Colour: JPEG, PDF, TIFF (JPEG)

Compression format: B/W: G4 (MMR), Colour: JPEG

Bundle software: KM-NET Viewer, TWAIN source

*Colour scanning at resolutions of 400 dpi and above requires additional memory.

Fax functions (optional)

Compatibility: ITU-T Super G3

Modem speed: Max. 33.6 kbps

Transmission speed: 3 seconds or less (JBIG)

Scanning density

Normal: 8 dot/mm x 3.85 line/mm, Fine: 8 dot/mm x 7.7 line/mm, Superfine: 8 dot/mm x 15.4 line/mm, Ultrafine: 16 dot/mm x 15.4 line/mm, SUFine: 600 x 600 dpi

Max. original size: A3

Compression method: JBIG, MMR, MR, MH

Memory: Standard 120 MB (enable fax image back-up)

Features: Internet fax, network fax, rotate transmission, confidential, relay and bulletin board transmission delivery to document box

Consumables

TK-675 Toner-Kit

Microfine toner for 20,000 pages with 6% coverage

Options

Fax System(M)2

Paper handling

DP-670 Document processor: 75 sheets, 45–160 g/m², A3–A5R, folio (RADF), colour scan

PF-670 Paper feeder: 2 x 500 sheets, 60–120 g/m², A3–B5R, letter, letter-R, legal, ledger, folio, STMT

DF-670(B) Internal document finisher: Max. 500 sheets A4 or 250 sheets A3, Folio, 60–105 g/m², one-position stapling max. 30 sheets A4 or 20 sheets A3

DF-730 Document finisher + AK-670*

Max. 1,000 sheets A4 or 500 sheets A3/B4, 64–128 g/m², A3–B5, one-position stapling max. 30 sheets A4 or 20 sheets A3–B4, 64–128 g/m²

JS-670(B) Job separator: 100 sheets internal job separator, 45–160 g/m², A3–A5R

*Adapter-Kit AK-670 is required for the use of DF-730 document finisher.

Memory

DIMM memory: 512 MB memory, DDR-SDRAM DIMM (100 pin): 2 slots (1 slot empty), max. 1 GB

CompactFlash® card

1 slot (up to 4 GB) for forms, fonts, logos, macro storage

BU-10 Back-up memory: 128 MB for fax box image back-up

Security

Data security kit (C)

UG-30: PDF expansion kit (high compression, encryption file)

Optional interface for print functions

PS159: Wireless LAN (802.11b/g)

PS1109 Gigabit Ethernet: 10BaseT/100BaseTX/1000BaseT (RJ-45)

PS129 Fibre Optic: 100BaseSX (SC)

PS1129 Gigabit Fibre Optic: 1000BaseSX (SC)

Others

Platen cover (D)

CB-670 Cabinet: Wooden desk with storage capacity

CB-671 Cabinet: Metal desk with storage capacity



KYOCERA MITA Europe B.V. – Branch Office Germany – Otto-Hahn-Straße 12 – 40670 Meerbusch – Germany
Tel +49 (0) 2159 928-500 – Fax +49 (0) 2159 918-100
www.kyoceramita-europe.com – info@kyoceramita-europe.com

KYOCERA MITA Corporation – 2-28, 1-Chome – Tamatsukuri – Chuo-Ku
Osaka 540-8585 – Japan – www.kyoceramita.com

** KYOCERA does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

KYOCERA